

MASTER AIR HOSE

(Complies to ISO 2398)



Common Applications

Heavy duty air supply line. Ideal for good performance in workshop and hire industries.

Tube

Black, SBR / NBR rubber, Oil mist resistant.

Reinforcement

High strength synthetic polyester braided.

Cover


Green, Blue, Red & Black, SBR / CR rubber, smooth surface, oil mist and weather resistant.

Temperature Range

- 20°C to + 80°C

Safety Factor

4 : 1



Product Code	Nominal inch	I.D. mm	O.D. mm	Working/Burst Pressure Bar	Weight Kg/Mt	Volume M ³	Coil Length Mt
RAD 10006	1/4	6.4	13.0	16 / 64	0.17	0.028	100
RAD 10008	5/16	8.0	15.0	16 / 64	0.21	0.035	100
RAD 10010	3/8	9.5	17.0	16 / 64	0.26	0.043	100
RAD 10013	1/2	12.7	22.0	16 / 64	0.42	0.077	100
RAD 10016	5/8	16.0	26.0	16 / 64	0.55	0.107	100
RAD 10019	3/4	19.0	29.0	16 / 64	0.63	0.130	100
RAD 10025	1	25.4	36.0	16 / 64	0.85	0.195	100

• Other sizes, colours and lengths available on request.