

ULTRA WATER SUCTION HOSE



Common Applications

A medium duty suction hose is suitable for use in agriculture, construction and mining industries. This hose is suitable for water and light slurry transfer in both negative and positive pressure applications.

Tube

Black SBR / NR rubber.

Reinforcement

Piles of high strength polyester cord incorporating a steel helix wire.

Cover

Black SBR / EPDM rubber, wrapped surface, abrasion and weather resistant.

Temperature Range

- 20°C to + 70°C.

Safety Factor

3 : 1

Product Code	Nominal inch	I.D. mm	O.D. mm	Working/Burst Pressure Bar	Weight Kg/Mt	Volume M ³	Coil Length Mt
RWS 1025	1	25.4	35.0	10 / 30	0.90	0.068	30 / 60
RWS 1032	1 1/4	32.0	42.0	10 / 30	1.11	0.094	30 / 60
RWS 1038	1 1/2	38.0	48.0	10 / 30	1.32	0.125	30 / 60
RWS 1050	2	51.0	62.0	10 / 30	1.95	0.237	30 / 60
RWS 1065	2 1/2	63.5	75.0	10 / 30	2.45	0.329	30 / 60
RWS 1075	3	76.0	89.0	10 / 30	3.35	0.507	30 / 60
RWS 1090	3 1/2	89.0	102.0	10 / 30	3.91	0.647	30 / 60
RWS 1100	4	102.0	117.0	10 / 30	5.23	0.992	30 / 60
RWS 1150	6	152.4	172.0	10 / 30	9.73	2.612	30 / 40
RWS 1200	8	203.0	225.0	10 / 30	12.30	5.695	30 / 40

• Other sizes, colours and lengths available on request.