

SAE 100 R7



Construction

- Core: Thermoplastic Elastomer
- Reinforcement : 1 braid of synthetic fibre
- Cover : Black colour, Pin Pricked - Polyurethane. Available twin and multi lines with different hose combination and size. Special colours and private print upon request.

Application and Temperature Range

- Medium Pressure Hydraulic Lines to 210 bar. Suitable for Hydraulic application with increased resistance to abrasion. For use with petroleum, synthetic or water based fluids in Hydraulic systems. Suitable for Agricultural machinery, Earthmoving, Telescopic booms and Material handling equipments. Can be used for industrial gases and other applications, please consult manufacturer.
- Temperature Standards: -40°C to +100°C (not to exceed +70°C for Air and water based fluids)

Size		I.D.		O.D.		Working Pressure		Min. Burst Pressure		Min. Bend Radius	
Dash	DN	inch	mm	inch	mm	PSI	in bar	PSI	in bar	mm	inch
2	3	1/8	3,2	0,32	8,1	3.000	210	12.000	840	25	1,0
4	6	1/4	6,4	0,49	12,4	2.750	190	11.000	760	32	1,3
6	10	3/8	9,6	0,62	15,7	2.250	155	9.000	620	55	2,2
10	16	5/8	15,9	0,91	23,1	1.500	105	6.000	420	110	4,4
16	25	1	25,4	1,31	33,3	1.000	70	4.000	280	200	8,0