

RADIATOR HOSE



Common Applications

Mandrel built straight radiator hose for the transfer of water in motor cooling systems.

Tube

Black EPDM rubber, heat resistant.

Reinforcement

Piles of high strength polyester cord.

Cover

Black EPDM Rubber, wrapped surface, heat and weather resistant.

Temperature Range

- 30°C to + 120°C

Safety Factor

3 : 1

Product Code	Nominal inch	I.D. mm	O.D. mm	Working/Burst Pressure Bar	Weight Kg/Mt	Volume M ³	Coil Length Mt
RSD 1025	1	25.0	35.0	10 / 30	0.60	0.001	1
RSD 1028	1 1/8	28.0	38.0	10 / 30	0.66	0.001	1
RSD 1032	1 1/4	32.0	42.0	10 / 30	0.74	0.002	1
RSD 1035	1 3/8	35.0	45.0	10 / 30	0.80	0.002	1
RSD 1038	1 1/2	38.0	48.0	10 / 30	0.86	0.002	1
RSD 1041	1 5/8	41.0	51.0	10 / 30	0.92	0.003	1
RSD 1044	1 3/4	44.0	55.0	10 / 30	1.09	0.003	1
RSD 1048	1 7/8	48.0	58.0	10 / 30	1.06	0.003	1
RSD 1050	2	51.0	62.0	10 / 30	1.24	0.004	1
RSD 1054	2 1/8	54.0	65.0	10 / 30	1.31	0.004	1
RSD 1057	2 1/4	58.0	69.0	10 / 30	1.40	0.005	1
RSD 1060	2 3/8	60.0	72.0	10 / 30	1.59	0.005	1
RSD 1065	2 1/2	63.5	76.0	10 / 30	1.68	0.006	1
RSD 1067	2 5/8	67.0	78.0	10 / 30	1.60	0.006	1
RSD 1070	2 3/4	70.0	82.0	10 / 30	1.83	0.007	1
RSD 1073	2 7/8	73.0	85.0	10 / 30	1.90	0.007	1
RSD 1075	3	76.0	88.0	10 / 30	1.97	0.008	1
RSD 1090	3 1/2	89.0	103.0	10 / 30	2.69	0.011	1
RSD 1100	4	102.0	114.0	10 / 30	2.60	0.013	1
RSD 1115	4 1/2	115.0	128.0	10 / 30	2.91	0.016	1
RSD 1125	5	127.0	140.0	10 / 30	3.48	0.020	1

• Other sizes, colours and lengths available on request.