

## SAE 100 R8



### Construction

- Core: Thermoplastic Elastomer
- Reinforcement : 1 braid of aramid fibre
- Cover : Black colour, Pin Pricked - Polyurethane. Available twin and multi lines with different hose combination and size. Special colours and private print upon request.

### Application and Temperature Range

- High Pressure Hydraulic Lines to 350 bar. Suitable for Hydraulic application with increased resistance to abrasion. For use with petroleum, synthetic or water based fluids in Hydraulic systems. Suitable for Agricultural machinery, Earthmoving, Telescopic booms and Material handling equipments. Can be used for industrial gases and other applications, please consult manufacturer.
- Temperature Standards: -40°C to +100°C (not to exceed +70°C for Air and water based fluids)

Size		I.D.		O.D.		Working Pressure		Min. Burst Pressure		Min. Bend Radius	
Dash	DN	inch	mm	inch	mm	PSI	in bar	PSI	in bar	mm	inch
3	5	3/16	4,8	0,49	12,4	5.000	350	20.000	1.400	40	1,6
5	8	5/16	8,0	0,66	16,7	4.250	290	17.000	1.160	55	2,2
8	12	1/2	12,7	0,89	22,6	3.500	245	14.000	980	77	3,1
12	20	3/4	19,1	1,14	28,9	2.250	155	9.000	620	140	5,6