

TWIN-LINE WELDING

(Complies to RMA Grade RM)



Common Applications

High performance dual extruded medium pressure hose is suitable for the transfer of oxygen and acetylene gas for welding and gas cutting applications.

Tube

Black SBR / NR blended.

Reinforcement

High strength synthetic polyester braided.

Cover

Green/Red, SBR/CR rubber, smooth surface, flame proof, abrasion and weather resistant.

Temperature Range

- 40°C to + 80°C.

Safety Factor

3 : 1

Product Code	Nominal inch	I.D. mm	O.D. mm	Working/Burst Pressure Bar	Weight Kg/Mt	Volume M ³	Coil Length Mt
RGD 5005/RM	$\frac{3}{16} + \frac{3}{16}$	5.0	12.0	20 / 60	0.33	0.041	100
RGD 5006/RM	$\frac{1}{4} + \frac{1}{4}$	6.3	13.0	20 / 60	0.36	0.059	100
RGD 5008/RM	$\frac{5}{16} + \frac{5}{16}$	8.0	15.0	20 / 60	0.44	0.073	100
RGD 5010/RM	$\frac{3}{8} + \frac{3}{8}$	10.0	17.0	20 / 60	0.52	0.083	100

- Other sizes, colours and lengths available on request.
- Apply to RMA Grade upon request.