

## BUNKERING HOSE 15 BAR

*(Complies to EN1765 type S15)*



### Common Applications

Hardwall hose used for the suction and discharge of petroleum products from tankers and barges, bunkering service and industrial applications; suitable for aromatic content up to 50%. Available with swaged-on fittings or built-in fittings.

### Tube

Black NBR rubber, oil resistant.

### Reinforcement

High strength synthetic cord, steel helix wire and anti-static copper wire.

### Cover

Black, smooth (wrapped finish), synthetic rubber resistant to weather, oil and sea water.

### Temperature Range

- 20°C to + 82°C

### Electrical characteristics

Electrically continuous.

### Safety Factor

4 : 1

Product Code	Nominal inch	I.D. mm	O.D. mm	Working/Burst Pressure Bar	Weight Kg/Mt	Volume M <sup>3</sup>	Coil Length Mt
RPS 4075	3	76.2	96.0	15 / 60	4.04	0.529	30 / 60
RPS 4100	4	101.6	126.0	15 / 60	6.50	1.152	30 / 60
RPS 4150	6	152.4	184.0	15 / 60	12.59	2.795	30 / 40
RPD 4200	8	203.0	238.0	15 / 60	18.55	6.024	30 / 40

• Other sizes, colours and lengths available on request.