

SAND BLAST HOSE



Common Applications

Abrasion resistant softwall hose, used for the delivery of sand or cast steel shot. It is manufactured with an anti-static rubber compound.

Tube

Black, smooth, anti-static SBR/NR rubber, abrasion resistant.

Reinforcement

High strength synthetic cord.

Cover

Black, smooth, (wrapped finish) anti-static SBR/NR rubber, abrasion resistant.

Temperature Range

- 30°C to + 70°C.

Safety Factor

3 : 1

Product Code	Nominal inch	I.D. mm	O.D. mm	Working/Burst Pressure Bar	Weight Kg/Mt	Volume M ³	Coil Length Mt
RHD 1013	1/2	13.0	27.0	10 / 30	0.55	0.043	30
RHD 1019	3/4	19.0	38.0	10 / 30	1.06	0.076	30
RHD 1025	1	25.4	39.0	10 / 30	0.85	0.094	30
RHD 1032	1 1/4	32.0	48.0	10 / 30	1.26	0.145	40
RHD 1037	1 1/2	38.0	56.0	10 / 30	1.64	0.170	30
RHD 1038	1 1/2	38.0	60.0	10 / 30	2.10	0.249	40
RHD 1050	2	51.0	72.0	10 / 30	2.54	0.280	30
RHD 1065	2 1/2	63.5	84.0	10 / 30	2.90	0.421	30
RHD 1075	3	76.0	96.0	10 / 30	3.37	0.544	30
RHD 1100	4	102.0	122.0	10 / 30	4.39	1.040	30

• Other sizes, colours and lengths available on request.