

BULK MATERIALS SUCTION HOSE



Common Applications

Dry materials suction and delivery hose is specially designed for transfer of dry cement, sand, gravel, feed, seed, etc by suction, gravity or by pneumatic systems.

Tube

Black NR / SBR rubber, abrasive resistant.

Reinforcement

High strength polyester cord plus helix wire and anti-static wire.

Cover

Black NR / SBR rubber, wrapped surface, weather and abrasion resistant.

Temperature Range

- 30°C to + 70°C.

Safety Factor

3 : 1

Product Code	Nominal inch	I.D. mm	O.D. mm	Working/Burst Pressure Bar	Weight Kg/Mt	Volume M ³	Coil Length Mt
RHS 1050	2	51.0	65.0	10 / 30	1.90	0.260	30 / 60
RHS 1065	2 ¹ / ₂	63.5	79.0	10 / 30	2.57	0.342	30 / 60
RHS 1075	3	76.0	92.0	10 / 30	3.13	0.950	30 / 60
RHS 1100	4	102.0	120.0	10 / 30	5.25	1.080	30 / 60
RHS 1125	5	127.0	147.0	10 / 30	6.38	2.233	30
RHS 1150	6	152.0	176.0	10 / 30	9.25	2.673	30

• Other sizes, colours and lengths available on request.