

## FOOD SUCTION & DELIVERY HOSE

*(Non-fatty Food Liquids)*



### Common Applications

Hardwall hose for suction and delivery of water, wine, juice, soft drinks, and other foodstuffs when a food quality hose is required. Not recommended for oily or fatty liquids.  
( Max 110°C for a few minutes with steam; max 30°C for a few minutes with 1% peracetic acid, 2% phosphoric acid, 5% caustic soda.)

### Tube

White, smooth, F.D.A. approved EPDM rubber.

### Reinforcement

High strength synthetic cord and helix wire

### Cover

Oxred, (wrapped finish), EPDM rubber, weather resistance.

### Temperature Range

- 35°C to + 100°C.

### Safety Factor

3 : 1

Product Code	Nominal inch	I.D. mm	O.D. mm	Working/Burst Pressure Bar	Weight Kg/Mt	Volume M <sup>3</sup>	Coil Length Mt
RFS 1025	1	25.0	38.0	10 / 30	1.01	0.081	30 / 60
RFS 1032	1 1/4	32.0	45.0	10 / 30	1.25	0.110	30 / 60
RFS 1038	1 1/2	38.0	52.0	10 / 30	1.59	0.133	30 / 60
RFS 1050	2	51.0	65.0	10 / 30	2.26	0.268	30 / 60
RFS 1065	2 1/2	63.5	80.0	10 / 30	3.06	0.342	30 / 60
RFS 1075	3	76.0	93.0	10 / 30	3.90	0.529	30 / 60
RFS 1100	4	102.0	120.0	10 / 30	5.33	1.080	30 / 60

• Other sizes, colours and lengths available on request.